

101401 EXTERIOR SIGNAGE

1. Kutztown University colors are as follows:
 - a. Maroon/Burgundy: PMS 195
 - b. Gold: PMS 123
2. Wayfinding and Facility Identification:
 - a. Refer to Appendix XII; Kutztown University Signage Standards Manual.
3. Traffic and Parking Control
 - a. Post: shall be a combination anchor post, sign post system connected by a breakaway connector. Posts are to be channel bar posts painted green meeting PennDOT standards and be compatible with the Minute Man connector specified below. Anchor post to be 3'6" in length and length of sign post will vary with application. Provide red reflector strips on STOP sign bar posts.
 - b. Breakaway connector: Use Marion Steel Minute Man System.
 - c. Installation:
 - a. Anchor post shall be poured in concrete with 3"- 4" of the remaining above grade. Concrete base shall be 8" in diameter and 3' below grade. Top edge to be chamfered.
 - b. Sign shall be mounted to the sign post and the sign post connected to the anchor post using breakaway connector specified above.
 - c. Where applicable, e.g. parking spaces, signs/posts shall be installed 3' from the edge of the pavement.
 - d. Traffic regulation signs, e.g. STOP, Do Not Enter, shall be installed so that the bottom of the sign is 7' above grade.