

265100 – INTERIOR LIGHTING

1.01 – SECTION INCLUDES

- A. Design standards for new construction and major renovations.
- B. Occupancy Sensor locations & types
- C. Light power density limits
- D. Special Use Spaces – All special use spaces are excluded from this guideline and shall be addressed on an individual basis and addressed during individual project design.

1.02 – REFERENCES

- A. Illuminating Engineering Society of North America (IESNA), Lighting Handbook, Ninth Edition
- B. ANSI/IESNA RP-3-00, Lighting for Educational Facilities
- C. ANSI/IESNA RP-16-05, Nomenclature and Definitions for Illuminating Engineering
- D. NECA/IESNA 500-2006, Standard for Installing Indoor Commercial Lighting System
- E. International Energy Conservation Code, latest edition

| Area | Recommended Footcandle Level | | CRI | CCT | Work plane Height (inches) | |
|-------------------------------|------------------------------|---------------------|--------|--------|----------------------------|----------|
| | Horizontal Work plane | Vertical Work plane | | | Horizontal | Vertical |
| Auditorium without Desktop | 10 | | 80-100 | 4200 K | 0 | |
| with Desktop | 30 | | 80-100 | 4200 K | 30 | |
| Lounge | 10 | 3 | 100 | 4200 K | 24-36 | 60-78 |
| Lobby | 10 | 3 | 100 | 4200 K | 0 | 60-78 |
| Reception Area | 10 | 3 | 100 | 4200 K | 36 | 60-78 |
| Conference Room General | 30 | 5 | 80 | 4200 K | 30 | 30-48 |
| Video Conference | 50 | 30 | 80 | 4200 K | 30 | 30-48 |
| Stairways and Corridors | 5 | 10 | 80 | 4200 K | 0 | 60-84 |
| Classroom | 30/50/100 | | 80 | 4200 K | 30 | |
| White Board | | 5 | | | | 36-60 |
| Chalk Board | | 50 | | | | 36-60 |

| | | | | | | |
|-------------------------|-----------|----|--------|--------|-------|---------|
| Art Classroom | 30/50/100 | 30 | (1) | (2) | 30 | 36-60 |
| Drafting | 30/50/100 | 10 | 80 | 4200 K | 30 | 36-60 |
| Family Consumer Science | 50 | 10 | 80 | 4200 K | 36 | 60-78 |
| Science Laboratory | 50 | 30 | 80 | 4200 K | 36-60 | 60-78 |
| Lecture Hall | | | | | | |
| Audience Area | 30 | | 80-100 | 4200 K | 30 | |
| Demonstration Area | 100 | 50 | 80-100 | 4200 K | 36 | 36-60 |
| Music | 30 | | 80 | 4200 K | 30 | |
| Gymnasium | | | | | | |
| Basketball | 100 | 30 | 80 | 4200 K | 0 | 110-150 |
| Social Events | 5 | 3 | 100 | 4200 K | 0 | 30-78 |
| Cafeteria Dining | | | | | | |
| | 10 | 3 | 80 | 4200 K | 30 | 30-48 |
| Cashier | 30 | 3 | 80 | 4200 K | 30 | 30-48 |
| Food Display | 50 | | 80 | 4200 K | 30 | 30-48 |
| Kitchen | 50 | 3 | 80 | 4200 K | 36 | 36-48 |

Design within the following Lighting Power Density limitations as per International Energy Conservation Code (IECC) Table 505.4.2, Interior Lighting Power Allowances, latest edition:

| Lighting Power Density | |
|-------------------------|-----------------------|
| Building Area Type | Watts/ft ² |
| Dining: Cafeteria | 1.4 |
| Dormitory | 1.0 |
| Exercise Center | 1.0 |
| Gymnasium | 1.1 |
| Library | 1.3 |
| Office | 1.0 |
| Performing Arts Theater | 1.6 |
| School/University | 1.2 |
| Workshop | 1.4 |

1.03 – CONTROL UNITS

When appropriate, interior lighting circuits shall include occupancy sensors as follows -

| Area | Occupancy Sensor Type |
|--------------------------------------|---|
| Office | Passive Infrared, Ultrasonic, Dual Technology |
| Mechanical Rooms | Dual Technology |
| Dormitory General Areas | Ultrasonic |
| Restrooms | Ultrasonic, Dual Technology |
| Laundry | Ultrasonic |
| Dwelling Area | Passive Infrared |
| Study Area | Dual Technology |
| Restrooms | Ultrasonic, Dual Technology |
| Maintenance Shops/Custodial Areas | Dual Technology |
| Storage | Passive Infrared, Ultrasonic |
| Cafeteria | Passive Infrared, Ultrasonic |
| Conference Room | Ultrasonic, Dual Technology |
| Classroom | Ultrasonic, Dual Technology |
| Closet | Passive Infrared, Ultrasonic |
| Corridor | Ultrasonic, Passive infrared, Dual Technology |
| Science Laboratory | Ultrasonic, Dual Technology |
| Gymnasium | Dual Technology |
| Lecture Hall | Dual Technology |
| Library Reading Stacks | Ultrasonic |
| Bookstack | Ultrasonic |
| Lobby | Passive Infrared, Dual Technology |
| Locker Room | Ultrasonic |